AD-A248 432

KEEP THIS COPY FOR REPRODUCTION PURPOSES

ATION PAGE

Form Approved OM8 No 0704-0186

o average 1 hour per response, including the time for reviewing instructions, searching existing data sources, ing the collection of information. Send comments regarding this burden estimate or any other aspect of this in to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson of Management and Budget, Paperwork Reduction Project (0704-0188). Washington: DC 20503

| March 1992 | Final | 15 Der 88-14 Dec 91 5. FUNDING NUMBERS |
|--|--|---|
| efects | | S. FUNDING NUMBERS |
| Micromechanics of Defects Author(S) | | |
| | | B. PERFORMING ORGANIZATION |
| = | | REPORT NUMBER |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P. O. Box 12211 Research Triangle Park, NC 27709-2211 | | 10. SPONSORING: MONITORING AGENCY REPORT NUMBER ARO 26057.16-EC |
| or findings contai | lned in this rep | ort are those of the |
| t be construed as | an official Dep | artment of the Army |
| EMENT | | 126. DISTRIBUTION CODE |
| | NC 27709-2211 or findings contact be construed as cision, unless so | or findings contained in this rept be construed as an official Depcision, unless so designated by o |

This report contains a brief outline of research findings and a list of publications and technical reports related to the project.



| Crack Arrest Mechanism, Composite Materials, Material Defects, Nondestructive Testing, Materials | | | 15. NUMBER OF PAGES 3 16. PRICE CODE | |
|--|--------------|--------------|--------------------------------------|--|
| | | | | |
| UNCLASSIFIED | UNCLASSIFIED | UNCLASSIFIED | UL | |

NSN 7540-01-280-5500

Standard Form 298 (Pey 200)

Brief Outlines of Research Findings

A physical explanation was given for the crack arrest mechanism in fiber reinforced composite materials. An award (Sawamura award) was given to this paper as the best paper in a year by Japan Society of Steels and Alloys.

Micromechanics of defects was studied completely in different direction (the inverse problem). This method provides a new approach of NDE (Nondestructive Evaluation) which can predict defects and integrity in materials or structures by knowing surface displacement change or measuring the surface tilts.

The most recent discovery is the following. When sliding occurs on the interface between matrix and inclusions (or inhomogeneities), the stress field $\tau_{ij}(x)$ can be expressed by a linear combination of Eshelby's solution $\sigma_{ij}^{E}(\mathbf{\epsilon}^{*})$ and Volterra's solution $\sigma_{ij}^{V}(\mathbf{b})$, i,e.,

$$\tau_{ij}(x) = \sigma_{ij}^{E}(\boldsymbol{\epsilon}^{*}) + s\sigma_{ij}^{V}(\mathbf{b}).$$

The factor s represents the degree of relaxation and it can explicitly be determined for the spherical sliding inclusions in terms of material constants.

Publications and technical reports related to this project are listed in a separated sheet.

The following post doctor fellows participated in this project:

Dr. T. Mori Professor, Tokyo Institute of Technology, Japan.

Dr. K. Tanaka Professor, Nagaoka Institute of Technology, Japan.

Dr. A. Sato Professor, Tokyo Institute of Technology, Japan.

92 4 10 022

92-09269


The following students participated and Ph.D. degree was awarded to them

Demitris Kourris Assistant Professor, Arizona State University.

Z. Gao Assistant Professor, Clarkson University, N.Y.

Iwona Jasiuk Assistant Professor, Michigan State University.

Professor Mura was made a honorary member of the Japan Institute of Metals Society due to his contributions to the field of metallurgy.



Proposal Number 26057-EG Funding Document DAAL03-89-k-0019

- 1. Axisymmetrically Loaded Thin Circular Plate in Adhesive Contact with an Elastic Half-Space, by E. N. Mastrojannis et al.
- 2. The Elastic Field of a Hemispherical Inhomogeneity at the Free Surface of an Elastic Half Space, by D. A. Kouris and T. Mura.
- 3. A Dislocation Model for Hardness Indentation Problems -- I, by T. Mura et al.
- 4. A Dislocation Model for Hardness Indentation Problems -- II, by K. Tanaka et al.
- 5. The Hemispheroidal Inhomogeneity at the Free Surface of an Elastic Half Space, by D. Kouris *et al.*
- 6. Impotent Dislocation Walls, by T. Mura.
- 7. Inverse Problem in Plasticity, by T. Mura and Z. Gao.
- 8. Crack Arrest by Strong Short Fibers in a Composite, by S. Shibata et al.
- 9. Near Threshold Fatigue Curve Based on the Dislocation Shielding Model of Fracture, by S. J. Chang and T. Mura.
- 10. Octahedral Defects in a b.c.c. Lattice Examined by Lattice Theory, by A. Sato et al.
- 11. Crack Branching Behavior in Stress Corrosion Cracking of High Strength Steel, by Y. Hirose and T. Mura.
- 12. Nonlinearity of Inverse Problems, by T. Mura and Z. Gao.
- 13. An Inverse Problem in Elasticity with Overprescribed Boundary Conditions, by Weichung Yeih et al.
- 14. Frictional Sliding Inclusions, by Jin H. Huang et al.